



# SAFETY DATA SHEET

## Section 1: Identification

Product Name: Mighty Level Compound  
 Product Code: DL6007  
 Product Class: Automotive Wax/Polishing Compound  
 Manufacturer/Supplier: Mighty Distributing System of America  
 650 Engineering Drive  
 Norcross, GA 30092  
 Telephone: 800-829-3900  
 Emergency Telephone: CHEMTREC 800-424-9300

Date Prepared: October 4, 2015  
 Date of Review/Update:

## Section 2: Hazard Identification

Classification of the chemical in accordance with paragraph (d) of §1910.1200:

### GHS Hazard Symbols:



GHS Classification: Flammable Liquid 3, Aspiration Toxicity 1, Eye and Skin Irritant 2b,  
Signal Word: Danger

### GHS Hazard Statements:

H226 Flammable liquid and vapor  
 H304 May be fatal if swallowed and enters airways  
 H315 Causes skin irritation  
 H320 Causes eye irritation

### GHS Precautionary Statements:

P101 If medical advice is needed, have product container or label at hand.  
 P102 Keep out of reach of children.  
 P202 Do not handle until all safety precautions have been read and understood.  
 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
 P280 Wear protective gloves/protective clothing/eye protection/face protection.  
 P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor  
 P308 + P313 IF exposed or concerned: Get medical advice/ attention.  
 P331 Do NOT induce vomiting.  
 P370 + P378 In case of fire: See Section 5 for extinguishing media.  
 P501 Dispose of contents/container to appropriate waste disposal facility, in accordance with local, regional, national and international regulations.

### Signs and Symptoms of Exposure:

Eye: Irritation including tearing or redness.  
 Skin: Prolonged skin contact may cause irritation including redness, irritation, itching.  
 Ingestion: Gastrointestinal irritation, nausea, vomiting, and diarrhea, upset stomach.  
 Inhalation: May cause allergy or asthma symptoms or breathing difficulties if inhaled..  
 Medical Conditions Aggravated by Exposure: None known.  
 HMIS Rating: Health- 1 Fire- 2 Reactivity- 0 Personal Protection- C

## Section 3: Composition/Information on Ingredients

<u>Chemical Name</u>	<u>CAS Number</u>	<u>% Range</u>	<u>OSHA PEL</u>	<u>ACGHI TLV</u>
Petroleum Distillates	64742-48-9	5-15	Not Established	Not Established
Alumina	1344-28-1	15-25	Not Established	Not Established
Petroleum Distillates	64742-47-8	5-15	Not Established	Not Established

## Section 4: First Aid Measures

Eye Contact: Flush with large amounts of water for 15 minutes. If symptoms persist, seek medical attention.  
Skin Contact: Wash affected area with water for 15 minutes. Remove contaminated clothing and launder before reuse.  
Ingestion: Never give anything by mouth to an unconscious person. If person is conscious then give several glasses of water. Do not induce vomiting. Keep warm and quiet. Seek medical attention.  
Inhalation: Remove from exposure. Seek fresh air. Keep warm and quiet. If symptoms persist seek medical attention.

### **Section 5: Fire-Fighting Measures**

Fire and Explosive Properties: Flash Point: 170°F / TCC Flammable Limits: LEL / UEL: 0.6 / 7.0  
Extinguishing Media: Water fog, dry chemicals or carbon dioxide.  
Special Fire Fighting Procedures: Full protective equipment including self-contained breathing apparatus for confined areas.  
Unusual Fire and Explosion Hazards: Vapors are heavier than air. Treat as petroleum fire.

### **Section 6: Accidental Release Measures**

Steps to be taken if Material is Spilled or Leaked: Remove all sources of ignition. Contain spill. Ventilate and remove with inert absorbent.

### **Section 7: Handling and Storage**

Precautions to be taken in Handling and Storage:

Contents may burn. Keep away from any heat or spark source. Do not smoke. Empty containers can contain explosive vapors. Never use a torch to cut or weld on or near container. Never wear oil soaked clothing. Launder or dry-clean before wearing. Discard oil soaked shoes. Affix proper warning labels on containers in accordance with 29CFR 1010.1200.

### **Section 8: Exposure Controls and Personal Protection**

Ventilation: Use only with adequate ventilation. Avoid breathing vapor or mist. Local exhaust preferred.  
Respirator Protection: Properly fitted NIOSH/MSHA approved respirator for ingredients found in SECTION 3 if TLV is exceeded.  
Skin Protection: Gloves rated for protection against ingredients in SECTION 3.  
Eye Protection: Safety glasses with side shields or chemical goggles.

### **Section 9: Physical and Chemical Properties**

Boiling Point:	212°F	Vapor Pressure (mmHg @ 68°F):	Unknown
Vapor Density:	Unknown	Solubility in Water:	Negligible
Specific Gravity:	1.01 ± 0.05	Melting Point:	Not Applicable
% Volatile:	75.0 ± 0.5	pH:	Not Applicable
Appearance/Odor:	Green Creamy Liquid, Watermelon Odor.		

### **Section 10: Stability and Reactivity**

Stability: Stable Materials to Avoid: Strong oxidizers  
Hazardous Polymerization: Will not occur. Conditions to Avoid: Open flames, sources of ignition.  
Hazardous Decomposition Products: Various hydrocarbons of incomplete combustion.

### **Section 11: Toxicology Information**

IARC, NTP, OSHA Carcinogen: None

### **Section 12: Ecological Information**

No data

### **Section 13: Disposal Considerations**

Waste Disposal: Waste from this product is hazardous (D001) as defined by the Resource Conservation and Recovery Act (RCRA) 40 CFR 261. Dispose of in accordance with federal, state and local regulations.

NOTE: Empty containers less than 110 gallons of D001 are not hazardous waste if as much of the product has been consumed as practical and less than 1 inch or 3% (by weight) of residue remain. (40CFR, 261.7)

### **Section 14: Transport Information**

D.O.T. REQUIREMENTS (49CFR 172.101):

Not regulated when shipped in quantities less than 119 gallons. If shipped in quantities of more than 119 gallons, or if shipped by vessel or aircraft use the following Proper Shipping Description (49CFR 173.120):

UN1993, Flammable Liquid N.O.S., 3, PG III, (Petroleum Distillates)

### **Section 15: Regulatory Information**

RQ (REPORTABLE QUANTITY) 49CFR 172.101:	None
TSCA (Toxic Substances Control Act) Status:	The intentional ingredients of this product are listed.
CERCLA RQ - 40CFR 302.4:	None
SARA 302 COMPONENTS - 40CFR 355 Appendix A:	None

SECTION 311/312 HAZARD CLASS - 40CFR 370.2

Immediate	(X)	Reactive	( )
Delayed	(X)	Sudden Release of Pressure	( )
Fire	(X)		

SARA 313 COMPONENTS - 40CFR 372.65: None

WORKPLACE HAZARDOUS INFORMATION SYSTEM (WHMIS)

<u>Ingredient</u>	<u>Cas Number</u>	<u>Max. % By Wt.</u>	<u>LD50</u>	<u>LC50</u>
Petroleum Distillates	64742-48-9	5-15	Not Established	Not Established
Alumina	1344-28-1	15-25	Not Established	Not Established
Petroleum Distillates	64742-47-8	5-15	Not Established	Not Established

CALIFORNIA PROPOSITION 65: None

**Section 16: Other Information**

Although the information contained herein is believed to be reliable, it is furnished without warranty of any kind. This information is not intended to be all-inclusive as to the manner and conditions of use, handling, and storage.