

SDS646 PRESTONE® COMMAND DIESEL EXHAUST FLUID

Date Prepared: 12/06/19

SAFETY DATA SHEET

1. Product And Company Identification

SDS ID: SDS646

PRODUCT NAME: Prestone ® COMMAND DIESEL EXHAUST FLUID

PRODUCT NUMBER: HD 1000, HD 1001, HD1000-330/1, HD1000-55, HD1000MB, HD1000M8, HD1000MTT

FORMULA NUMBER: 2590-30, 2591-31

MANUFACTURER: CANADIAN OFFICE: MEXICO OFFICE:

Prestone Products Prestone Canada ASG Operations Mexico S. de R.L. de C.V.

Corporation 33 MacIntosh Blvd. Carretera Mexico Cuautitlan, Kilometro 31.5, Nave

69 Eagle Rd. Concord, ON L4K 4L5 Industrial 5,

Danbury, CT 06810 Loma Bonita, Cuautitlan, Mexico, 54800

MEDICAL EMERGENCIES AND ALL OTHER INFORMATION PHONE NUMBER:

(888)269-0750 (in the US and Canada)

01-800-715-4135 (in Mexico)

TRANSPORTATION EMERGENCY PHONE NUMBER (Chemical Spills and Transport Accidents only):

CHEMTREC 1-800-424-9300 (in the US and Canada) +1 703 741-5970 (outside the US and Canada)

PRODUCT USE: Diesel fuel additive – consumer product

RESTRICTIONS ON USE: None identified

2. Hazards Identification

GHS Classification:

Health	Environmental	Physical
Not Hazardous	Not Hazardous	Not Hazardous

Label Elements: None

3. Composition/Information On Ingredients

Component	CAS No.	Amount
Water	7732-18-5	60-70%
Urea	57-13-6	30-40%

The exact concentrations are a trade secret.

4. First Aid Measures

INHALATION: Remove victim to fresh air. Obtain medical attention if irritation occurs or persists.

SKIN CONTACT: Removed contaminated clothing immediately. Wash skin thoroughly with soap and water. Obtain medical attention if irritation occurs or persists.

EYE CONTACT: Exposed eyes should be flushed with copious amounts of water using a steady stream for several minutes. If irritation, pain, swelling or tearing persist, seek medical attention.



PRESTONE® COMMAND DIESEL EXHAUST FLUID

Date Prepared: 12/06/19

INGESTION: If swallowed, get immediate medical advice by calling a Poison Control Center, or emergency room. If advice is not available, take victim and product container to the nearest emergency treatment center or hospital. Do not attempt to give anything by mouth to an unconscious person.

MOST IMPORTANT SYMPTOMS: May cause slight eye and skin irritation. Ingestion may cause gastrointestinal irritation.

INDICATION OF IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT, IF NEEDED: None known.

NOTES TO PHYSICIAN: Treatment of overexposure should be directed at the control of symptoms and the clinical conditions.

5. Firefighting Measures

SUITABLE EXTINGUISHING MEDIA: This product is not combustible. Use any media that is appropriate for the surrounding fire.

SPECIFIC HAZARDS ARISING FROM THE CHEMICAL: Thermal decomposition may produce oxides of nitrogen.

SPECIAL PROTECTIVE EQUIPMENT AND PRECAUTIONS FOR FIRE FIGHTERS: Firefighters should wear positive pressure self- contained breathing apparatus and full protective clothing for fires in areas where chemicals are used or stored.

6: Accidental Release Measures

PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES: Wear appropriate protective clothing and equipment (See Section 8).

METHODS AND MATERIALS FOR CONTAINMENT/CLEANUP: Collect with absorbent material and place in appropriate, labeled container for disposal or, if permitted flush spill area with water.

7. Handling and Storage

PRECAUTIONS FOR SAFE HANDLING: Avoid eye, and prolonged or repeated skin contact. Do not reuse empty containers unless properly cleaned.

CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES: Store in a cool, dry area.

NFPA CLASSIFICATION: IIIB

8. Exposure Controls / Personal Protection

EXPOSURE GUIDELINES

CHEMICAL	EXPOSURE LIMIT
Water	None Established (PEL/TLV)
Urea	10 mg/m3 TWA AIHA WEEL

APPROPRIATE ENGINEERING CONTROLS: Use general ventilation or local exhaust as required to maintain exposures below the occupational exposure limits.

PERSONAL PROTECTIVE EQUIPMENT

RESPIRATORY PROTECTION: None needed under normal conditions of use.

GLOVES: None normally needed. For prolonged contact rubber or neoprene gloves can be worn.

SDS646 PRESTONE® COMMAND DIESEL EXHAUST FLUID

Date Prepared: 12/06/19

EYE PROTECTION: Safety glasses recommended if splashing is possible.

OTHER PROTECTIVE EQUIPMENT/CLOTHING: Appropriate protective clothing as needed to minimize skin contact.

9. Physical and Chemical Properties

APPEARANCE:	Clear liquid	ODOR:	Not determined
ODOR THRESHOLD:	Not determined	pH:	9.3 - 9.8
MELTING/FREEZING	11.3 to 11.5°F	BOILING POINT/RANGE:	220°F (104.4°C)
POINT:	(-11.5 to -11.4°C)		
FLASH POINT:	None to 216°F (>102.2°C)	EVAPORATION RATE:	Not determined
	Setaflash		
FLAMMABILITY (SOLID,	Non-Flammable	FLAMMABILITY LIMITS:	LEL: Not applicable
GAS)			UEL: Not applicable
VAPOR PRESSURE:	Not determined	VAPOR DENSITY:	Not determined
RELATIVE DENSITY:	1.091 – 1.092	SOLUBILITIES	Water: 100%
PARTITION COEFFICIENT	Not determined	AUTOIGNITION	Not applicable
(n-octanol/water)		TEMPERATURE:	
DECOMPOSITION	Not determined	VISCOSITY (Cst @ 68°F):	Not determined
TEMPERATURE:			

10. Stability and Reactivity

REACTIVITY: Normally unreactive

CHEMICAL STABILITY: Stable

POSSIBILITY OF HAZARDOUS REACTIONS: None known

CONDITIONS TO AVOID: None known

INCOMPATIBLE MATERIALS: Strong acids, and oxidizers.

HAZARDOUS DECOMPOSITION PRODUCTS: Thermal decomposition may produce oxides of nitrogen.

11. Toxicological Information

POTENTIAL HEALTH EFFECTS:

ACUTE HAZARDS:

INHALATION: Inhalation is not expected to be hazardous. Inhalation of large amounts of mist may cause mucous membrane irritation.

SKIN CONTACT: Skin contact is not expected to be hazardous. Prolonged or excessive contact may cause skin irritation.

EYE CONTACT: Liquid or mist may cause discomfort in the eye with persistent conjunctivitis, seen as slight excess redness or conjunctiva.

INGESTION: Ingestion of small amounts is not expected to be acutely hazardous. Ingestion of large amounts may cause gastrointestinal irritation.

CHRONIC HAZARDS: None currently known.



PRESTONE® COMMAND DIESEL EXHAUST FLUID

Date Prepared: 12/06/19

SDS646

CARCINOGENICITY LISTING: None of the ingredients are listed as a carcinogen or potential carcinogen by IARC, NTP, ACGIH, or OSHA.

ACUTE TOXICITY VALUES:

Urea: LD50 Oral Rat: 8471 mg/kg

12. Ecological Information

ECOTOXICITY: No ecotoxicity data is available at this time.

PERSISTENCE AND DEGRADABILITY: Urea is rapidly hydrolyzed to ammonia and carbon dioxide in environmental systems by the extracellular enzyme, urease, which originates from microorganisms and plant roots.

BIOACCUMULATIVE POTENTIAL: Urea: The potential for bioconcentration in aquatic organisms is low.

MOBILITY IN SOIL: Urea: Very high mobility in soil.

OTHER ADVERSE EFFECTS: None known

13. Disposal Considerations

Dispose of product in accordance with all local, state/provincial and federal regulations.

14. Transport Information

U.S. DOT HAZARD CLASSIFICATION: Not Regulated

DOT MARINE POLLUTANTS: This product does not contain Marine Pollutants as defined in 49 CFR 171.8.

IMDG CODE SHIPPING CLASSIFICATION: Not Regulated

CANADIAN TDG CLASSIFICATION: Not Regulated

15. Regulatory Information

EPA SARA 311/312 HAZARD CLASSIFICATION: Refer to Section 2 for the OSHA Hazard Classification.

EPA SARA 313: This Product Contains the Following Chemicals Subject to Annual Release Reporting Requirements Under SARA Title III, Section 313 (40 CFR 372): None

PROTECTION OF STRATOSPHERIC OZONE: This product is not known to contain or to have been manufactured with ozone depleting substances as defined in 40 CFR Part 82, Appendix A to Subpart A.

CERCLA SECTION 103: This product is not subject to CERCLA reporting requirements, however, many states have more stringent release reporting requirements. Report spills required under federal, state and local regulations.

CALIFORNIA PROPOSITION 65: This product does not contain chemicals regulated under California Proposition 65.

EPA TSCA INVENTORY: All of the components of this material are listed on the Toxic Substances Control Act (TSCA) Chemical Substances Inventory.

CANADIAN ENVIRONMENTAL PROTECTION ACT: All of the ingredients are listed on the Canadian Domestic Substances List.



SDS646 PRESTONE® COMMAND DIESEL EXHAUST FLUID

Date Prepared: 12/06/19

EUROPEAN INVENTORY OF EXISTING COMMERCIAL CHEMICAL SUBSTANCES (EINECS): All of the ingredients are listed on the EINECS inventory.

AUSTRALIA: All of the ingredients of this product are listed on the Australian Inventory of Chemical Substances.

NEW ZEALAND All of the ingredients of this product are listed on the Hazardous Substance and New Organisms list (HSNO)

JAPAN: All of the ingredients of this product are listed on the Japanese Existing and New Chemical Substances (METI) List.

KOREA: All of the ingredients of this product are listed on the Korean Existing Chemical List (KECL).

CHINA. All of the ingredients of this product are listed on the Inventory of Existing Chemical Substances in China (IECSC).

PHILIPPINES: All of the ingredients of this product are listed on the Philippine Inventory of Chemical and Chemical Substance (PICCS)

16. Other Information

NFPA RATING (NFPA 704) - FIRE: 0

HEALTH: 1

REACTIVITY: 0

REVISION SUMMARY: Section 5: Fire Fighting Measures, Section 7: NFPA CLASSIFICATION, Section 15: added EPA SARA 311/312 HAZARD CLASSIFICATION

SDS Date of Preparation/Revision: December 6, 2019

This SDS is directed to professional users and bulk handlers of the product. Consumer products are labeled in accordance with Federal Hazardous Substances Act regulations.

While Prestone Products Corporation believes that the data contained herein are factual and the opinions expressed are those of qualified experts regarding the results of the tests conducted, the data are not to be taken as a warranty or representation for which Prestone Products Corporation assumes legal responsibility. They are offered solely for your consideration, investigation and verification. Any use of these data and information must be determined by the user to be in accordance with applicable federal, state and local laws and regulations.