



Mighty Professional Gasoline Intake Cleaner

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Issue date: 12/22/2020

Version: 1.0

SECTION 1: Identification

1.1. Identification

Product form : Mixture
 Trade name : Mighty Professional Gasoline Intake Cleaner
 Synonym : 0700214
 Part numbers : FL135

1.2. Recommended use and restrictions on use

1.3. Supplier

Manufacturer

Gold Eagle Co
 4400 S Kildare Ave
 Chicago, IL 60632-4372
 T 773-376-4400
<https://www.goldeagle.com/>

1.4. Emergency telephone number

Emergency number : INFOTrac: 1-800-535-5053

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Flammable liquids Category 3	H226	Flammable liquid and vapor
Acute toxicity (inhalation:dust,mist) Category 4	H332	Harmful if inhaled
Skin corrosion/irritation Category 2	H315	Causes skin irritation
Serious eye damage/eye irritation Category 2	H319	Causes serious eye irritation

Full text of H statements : see section 16

2.2. GHS Label elements, including precautionary statements

GHS US labeling

Hazard pictograms (GHS US) :



Signal word (GHS US) :

Danger

Hazard statements (GHS US) :

H226 - Flammable liquid and vapor
 H315 - Causes skin irritation
 H319 - Causes serious eye irritation
 H332 - Harmful if inhaled

Precautionary statements (GHS US) :

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P233 - Keep container tightly closed.
 P240 - Ground/Bond container and receiving equipment.
 P241 - Use explosion-proof electrical/ventilating/lighting equipment.
 P242 - Use only non-sparking tools.
 P243 - Take precautionary measures against static discharge.
 P261 - Avoid breathing dust/fume/gas/mist/vapors/spray.
 P264 - Wash hands, forearms and face thoroughly after handling.
 P271 - Use only outdoors or in a well-ventilated area.
 P280 - Wear protective gloves/protective clothing/eye protection/face protection.
 P302+P352 - If on skin: Wash with plenty of water.
 P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse

Mighty Professional Gasoline Intake Cleaner

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

skin with water/shower.

P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P312 - Call a poison center or doctor if you feel unwell.

P321 - Specific treatment (see supplemental first aid instruction on this label).

P332+P313 - If skin irritation occurs: Get medical advice/attention.

P337+P313 - If eye irritation persists: Get medical advice/attention.

P362+P364 - Take off contaminated clothing and wash it before reuse.

P370+P378 - In case of fire: Use media other than water to extinguish.

P403+P235 - Store in a well-ventilated place. Keep cool.

P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS US classification
Ethylene glycol monobutyl ether	(CAS-No.) 111-76-2	30 – 40	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319
Xylene	(CAS-No.) 1330-20-7	30 – 40	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315
Triethanolamine	(CAS-No.) 102-71-6	0 – 10	Not classified
Proprietary		0 – 10	Not classified
Proprietary additive		0 – 10	Not classified

*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

4.2. Most important symptoms and effects (acute and delayed)

Potential Adverse human health effects and symptoms : Causes serious eye irritation. Causes severe skin burns. Causes serious eye damage. Causes damage to organs if swallowed. May be fatal if swallowed and enters airways.

4.3. Immediate medical attention and special treatment, if necessary

No additional information available

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

5.2. Specific hazards arising from the chemical

5.3. Special protective equipment and precautions for fire-fighters

No additional information available

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

No additional information available

Mighty Professional Gasoline Intake Cleaner

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

6.1.2. For emergency responders

6.2. Environmental precautions

No additional information available

6.3. Methods and material for containment and cleaning up

6.4. Reference to other sections

No additional information available

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : Flammable vapors may accumulate in the container.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Store in a well-ventilated place. Keep container tightly closed.
Incompatible products : Oxidizing agent. Strong acids. Strong bases.
Incompatible materials : Sources of ignition. Heat sources. Direct sunlight.
Storage area : Keep only in the original container. Store in a cool area. Store in a well-ventilated place.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Mighty Professional Gasoline Intake Cleaner	
No additional information available	
Ethylene glycol monobutyl ether (111-76-2)	
USA - ACGIH - Occupational Exposure Limits	
Local name	2-Butoxyethanol (EGBE)
ACGIH TWA (ppm)	20 ppm
Remark (ACGIH)	TLV® Basis: Eye & URT irr. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans); BEI
Regulatory reference	ACGIH 2019
USA - OSHA - Occupational Exposure Limits	
Local name	2-Butoxyethanol
OSHA PEL (TWA) (mg/m³)	240 mg/m³
OSHA PEL (TWA) (ppm)	50 ppm
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
Proprietary	
No additional information available	
Proprietary additive	
No additional information available	
Xylene (1330-20-7)	
USA - OSHA - Occupational Exposure Limits	
Local name	Xylenes (o-, m-, p-isomers)
OSHA PEL (TWA) (mg/m³)	435 mg/m³
OSHA PEL (TWA) (ppm)	100 ppm
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
Triethanolamine (102-71-6)	
No additional information available	

8.2. Appropriate engineering controls

Mighty Professional Gasoline Intake Cleaner

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Gloves. In case of splash hazard: safety glasses. Safety glasses. Wear recommended personal protective equipment.

Personal protective equipment symbol(s):



SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Liquid.
Color	: Amber to brown
Odor	: Amine-like
Odor threshold	: No data available
pH	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: No data available
Vapor pressure	: No data available
Relative vapor density at 20 °C	: No data available
Relative density	: ≈ 0.9
Specific gravity / density	: ≈ 7.5 lb/gal
Solubility	: Poorly soluble in water.
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: ≈ 3 mm ² /s
Viscosity, dynamic	: No data available
Explosion limits	: No data available
Explosive properties	: No data available.
Oxidizing properties	: No data available.

9.2. Other information

VOC content : ≈ 100 %

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

10.3. Possibility of hazardous reactions

No additional information available

10.4. Conditions to avoid

No additional information available

10.5. Incompatible materials

No additional information available

Mighty Professional Gasoline Intake Cleaner

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

10.6. Hazardous decomposition products

No additional information available

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Harmful if inhaled.

ATE US (dust, mist)	1.875 mg/l/4h
---------------------	---------------

Ethylene glycol monobutyl ether (111-76-2)	
LD50 oral rat	1746 mg/kg body weight (Equivalent or similar to OECD 401, Rat, Male, Experimental value, Oral)
LD50 dermal rat	> 2000 mg/kg body weight (OECD 402: Acute Dermal Toxicity, Rat, Male / female, Experimental value, Dermal, 14 day(s))
LC50 Inhalation - Rat [ppm]	450 ppm (Equivalent or similar to OECD 403, 4 h, Rat, Female, Experimental value, Inhalation (vapours))

Xylene (1330-20-7)	
LD50 oral rat	3523 mg/kg body weight (Equivalent or similar to EU Method B.1: Acute Toxicity (Oral), Rat, Male, Experimental value, Oral, 14 day(s))

Skin corrosion/irritation : Causes skin irritation.
Serious eye damage/irritation : Causes serious eye irritation.
Respiratory or skin sensitization : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified

Ethylene glycol monobutyl ether (111-76-2)	
IARC group	3 - Not classifiable

Xylene (1330-20-7)	
IARC group	3 - Not classifiable

Reproductive toxicity : Not classified

STOT-single exposure : Not classified

STOT-repeated exposure : Not classified

Aspiration hazard : Not classified
Viscosity, kinematic : $\approx 3 \text{ mm}^2/\text{s}$

Likely routes of exposure : Dermal. Inhalation. Skin and eye contact.
Potential Adverse human health effects and symptoms : Causes serious eye irritation. Causes severe skin burns. Causes serious eye damage. Causes damage to organs if swallowed. May be fatal if swallowed and enters airways.

SECTION 12: Ecological information

12.1. Toxicity

Ethylene glycol monobutyl ether (111-76-2)	
LC50 fish 1	1474 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Oncorhynchus mykiss, Static system, Fresh water, Experimental value, Nominal concentration)
EC50 Daphnia 1	1550 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, Nominal concentration)

Xylene (1330-20-7)	
LC50 fish 1	2.6 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Oncorhynchus mykiss, Static renewal, Fresh water, Read-across, Lethal)

Mighty Professional Gasoline Intake Cleaner

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Xylene (1330-20-7)	
ErC50 (algae)	4.36 mg/l (OECD 201: Alga, Growth Inhibition Test, 73 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, GLP)

12.2. Persistence and degradability

Ethylene glycol monobutyl ether (111-76-2)	
Persistence and degradability	Readily biodegradable in water.

Xylene (1330-20-7)	
Persistence and degradability	Biodegradable in the soil. Readily biodegradable in water.

12.3. Bioaccumulative potential

Ethylene glycol monobutyl ether (111-76-2)	
Partition coefficient n-octanol/water (Log Pow)	0.81 (Test data, 20 °C)
Partition coefficient n-octanol/water (Log Kow)	0.83
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

Xylene (1330-20-7)	
BCF fish 1	7.2 – 25.9 (56 day(s), Oncorhynchus mykiss, Flow-through system, Fresh water, Read-across)
Partition coefficient n-octanol/water (Log Pow)	3.2 (Read-across, 20 °C)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).

Triethanolamine (102-71-6)	
Partition coefficient n-octanol/water (Log Kow)	-1

12.4. Mobility in soil

Ethylene glycol monobutyl ether (111-76-2)	
Surface tension	65.03 mN/m (20 °C, 2 g/l)
Ecology - soil	Low potential for adsorption in soil.

Xylene (1330-20-7)	
Surface tension	28.01 – 29.76 mN/m (25 °C)
Partition coefficient n-octanol/water (Log Koc)	2.73 (log Koc, Equivalent or similar to OECD 121, Read-across)
Ecology - soil	Low potential for adsorption in soil. May be harmful to plant growth, blooming and fruit formation.

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Disposal methods

Regional legislation (waste)	: Disposal must be done according to official regulations.
Sewage disposal recommendations	: Disposal must be done according to official regulations.
Product/Packaging disposal recommendations	: Remove waste in accordance with local and/or national regulations.
Additional information	: Flammable vapors may accumulate in the container.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Not applicable

Mighty Professional Gasoline Intake Cleaner

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 15: Regulatory information

15.1. US Federal regulations

Mighty Professional Gasoline Intake Cleaner

Subject to reporting requirements of United States SARA Section 313

Ethylene glycol monobutyl ether (111-76-2)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Xylene (1330-20-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Subject to reporting requirements of United States SARA Section 313

Listed on EPA Hazardous Air Pollutant (HAPS)

CERCLA RQ

100 lb

15.2. International regulations

CANADA

Ethylene glycol monobutyl ether (111-76-2)

Listed on the Canadian DSL (Domestic Substances List)

Xylene (1330-20-7)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

No additional information available

National regulations

No additional information available

15.3. US State regulations

No additional information available

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full text of H-phrases:

H226	Flammable liquid and vapor
H302	Harmful if swallowed
H312	Harmful in contact with skin
H315	Causes skin irritation
H319	Causes serious eye irritation
H332	Harmful if inhaled

SDS US (GHS HazCom 2012)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.